


SOT-23 Plastic-Encapsulate MOSFETS

TF2302G

TF2302G N-Channel 20-V(D-S) MOSFET

V_{(BR)DSS}	R_{D(on)MAX}	I_D
20V	0.050Ω@ 4.5V	3A
	0.065Ω@ 2.5V	



General FEATURE

- TrenchFET Power MOSFET
- Lead free product is acquired
- Surface mount package

APPLICATION

- Load Switch for Portable Devices
- DC/DC Converter

Maximum ratings ($T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	20	V
Gate-Source Voltage	V _{GS}	±10	
Continuous Drain Current	I _D	3.0	A
Pulsed Drain Current*1	I _{DM}	10	
Continuous Source-Drain Diode Current	I _S	1.0	
Maximum Power Dissipation	P _D	1.0	W
Thermal Resistance from Junction to Ambient($t \leq 5\text{s}$)	R _{θJA}	156	°C/W
Junction Temperature	T _J	150	°C
Storage Temperature	T _{stg}	-55 ~+150	

Note :

*1. Pulse Width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$

SOT-23 Plastic-Encapsulate MOSFETS

TF2302G

MOSFET ELECTRICAL CHARACTERISTICS

T_a = 25 °C unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Static						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	20			V
Gate-source threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	0.5	0.8	1.0	
Gate-source leakage	I _{GSS}	V _{DS} = 0V, V _{GS} = ±10V			±100	nA
Zero gate voltage drain current	I _{DSS}	V _{DS} = 16V, V _{GS} = 0V			1	μA
Drain-source on-state resistance ^a	R _{DSS(on)}	V _{GS} = 4.5V, I _D = 3A		0.045	0.055	Ω
		V _{GS} = 2.5V, I _D = 2A		0.050	0.055	
Forward transconductance ^a	g _{fs}	V _{DS} = 5V, I _D = 3A		8.0	-	S
Dynamic^b						
Input capacitance	C _{iss}	V _{DS} = 10V, V _{GS} = 0V, f = 1MHz		300		pF
Output capacitance	C _{oss}			120		
Reverse transfer capacitance	C _{rss}			80		
Total gate charge	Q _g	V _{DS} = 10V, V _{GS} = 4.5V, I _D = 3A		4.0		nC
Gate-source charge	Q _{gs}			0.65		
Gate-drain charge	Q _{gd}			1.6		
Turn-on delay time	t _{d(on)}	V _{DD} = 10V, I _D = 3A V _{GEN} = 4.5V, R _g = 6Ω		15.0		ns
Rise time	t _r			85.0		
Turn-off delay time	t _{d(off)}			45.0		
Fall time	t _f			20.0		
Drain-source body diode characteristics						
Continuous source-drain diode current	I _s	T _c = 25°C			1.0	A
Body diode voltage	V _{SD}	I _s = 1.0A		0.7	1.3	

Notes :

a. Pulse Test : Pulse Width < 300μs, Duty Cycle ≤ 2%.

b. Guaranteed by design, not subject to production testing.

SOT-23 Plastic-Encapsulate MOSFETS

TF2302G

Typical Electrical and Thermal Characteristics




Figure 1:Switching Test Circuit






Figure 2:Switching Waveforms




T_j-Junction Temperature(°C)

Figure 3 Power Dissipation




T_j-Junction Temperature(°C)

Figure 4 Drain Current



V_{DS} Drain-Source Voltage (V)

Figure 5 Output Characteristics



I_D- Drain Current (A)

Figure 6 Drain-Source On-Resistance

SOT-23 Plastic-Encapsulate MOSFETS

TF2302G




Figure 7 Transfer Characteristics




Figure 8 Drain-Source On-Resistance




Figure 9 $R_{DS(on)}$ vs V_{GS}




Figure 10 Capacitance vs V_{DS}




Figure 11 Gate Charge






Figure 12 Source- Drain Diode Forward

SOT-23 Plastic-Encapsulate MOSFETS


TF2302G



SOT-23 Plastic-Encapsulate MOSFETS


TF2302G

SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.